

MONITORING OF PRESSING PROCESS IN ADVANCED FORMWORK COMPOSITES II.

2017, September 6th Zagreb, University of Zagreb, Faculty of Forestry

Roman Réh, Assoc. Prof., PhD. Technical University in Zvolen, Slovakia





INTRODUCTION

- Monitoring of Pressing Process in Advanced Formwork Composites I.
- Published in the Proceedings from the COST Action FP1303 Conference in Kranjska Gora in 2014
- The aim of our long-term research: to optimize the pressing process of wood composites used for the production of formwork.
- This second part of the research is aimed to the evaluation of the mechanical properties of formwork composites produced as the result of time optimization of the technological operation of their pressing


- four structures of three-layer formwork composites
- spruce slats with a thickness of 9 mm were used in all structures as the core layer
- surface layer were formed by four alternatives:
 - a. 3-ply birch plywood, thickness of 4 mm (PL 4)b. 3-ply birch plywood thickness of 6 mm (PL 6)
 - c. OSB thickness of 6 mm (OSB)
 - d. RB1 and RB2 reference type of boards with spruce slats of 6 mm in the surface layer pressed in the laboratory or taken from the factory and just tested in the laboratory

RESULTS AND DISCUSSION





RESULTS AND DISCUSSION



Bonding test of the four formwork composites depending on the alternative surface layers used (Zwick/Roell Z020)

CONCLUSIONS

- 3-layer composite formwork should have firm solid surface layers
- birch plywood is a suitable material for this purpose



Thank you for your attention.

Roman Réh, Assoc. Prof., PhD. Technical University in Zvolen Faculty of Wood Science and Technology SK-960 53 Zvolen <u>reh@tuzvo.sk</u>

Acknowledgements

The research described in the paper presented was supported by the Slovak Research and Development Agency under the contract No. APVV-14-0506 and APVV-0200-12. The author would like to thank the agency for the support of this research.